



Panel Grade	Point Load	Load Over	UDL	Panel Thickness (Nominal)	System Weight (Typical)
Medium	3kN	4.5kN	8.0kN/m <sup>2</sup>	31MM	33kg/m <sup>2</sup>

#### ▼ RFS-MES Medium Grade Panel

This panel consists of a high grade 30mm chipboard core with steel top sheet and bottom tray all roll formed together creating a fully steel encapsulated panel with predrilled holes to be screw fixed with complete electrical continuity. The screw down panel gives added stability and security as the void is inaccessible without specialist tools.

#### ▼ Certification

The panel has been fully tested by a NAMAS accredited laboratory to the MOB PSA PF2 PS/SPU March 1992 Medium Grade specification and is certified as being fully compliant. All PSA panels have a 3 times working load safety factor, class '0' spread of flame resistance and 25 year guarantee.

#### ▼ Finish

All of our steel encapsulated panels are designed to be overlaid with finishes by others such as loose laid carpet tiles. Whatever your requirements, Raised Floor Systems will have the flooring solution to suit you.

#### ▼ Manufacture

All panels are manufactured in the UK, which allows us to offer total flexibility whilst maintaining the highest possible quality standard and ensures fast reaction and a reliable service. Materials used are sourced from high quality suppliers and use renewable, sustainable sources and suppliers wherever possible. We can also offer a bespoke service and specialise in replicating and reproducing existing raised floors.

#### ▼ Accessories

Accessories include ramps, steps, handrails, subfloor seal, fire barrier, grilles, up stands, perforated panels, air leakage control, bridging, stringers, service outlets, cavity barrier and lifting tools.

**FULL DETAILS AVAILABLE ON REQUEST**

#### Raised Floor Systems Limited

Unit 3 Henlow Industrial Estate  
Henlow Camp  
Bedfordshire SG16 6DS

+44 (0)1462 685 898  
enquiries@raisedfloorsystems.co.uk  
www.raisedfloorsystems.co.uk